


# THE ALLMAX

## 1500V MODULE



**60 CELL**  
MULTICRYSTALLINE MODULE

**260-270W**  
POWER OUTPUT RANGE

**16.5%**  
MAXIMUM EFFICIENCY

**0~+5W**  
POSITIVE POWER TOLERANCE

As a leading global manufacturer of next generation photovoltaic products, we believe close cooperation with our partners is critical to success. With local presence around the globe, Trina is able to provide exceptional service to each customer in each market and supplement our innovative, reliable products with the backing of Trina as a strong, bankable partner. We are committed to building strategic, mutually beneficial collaboration with installers, developers, distributors and other partners as the backbone of our shared success in driving Smart Energy Together.

Trina Solar Limited  
www.trinasolar.com



### Ideal for large scale installations

- High power footprint reduces installation time and BOS costs
- UL1500V/IEC1500V certified



### One of the industry's most trusted modules

- Field proven performance



### Highly reliable due to stringent quality control

- Over 30 in-house tests (UV, TC, HF, and many more)
- In-house testing goes well beyond certification requirements
- PID resistant
- 100% EL double inspection




### Certified to withstand challenging environmental conditions

- 2400 Pa wind load
- 5400 Pa snow load
- 35 mm hail stones at 97km/h

## Comprehensive products and system certificates

- IEC 61215/ IEC 61730/ UL 1703/ IEC 61701/IEC 62716
- ISO 9001: Quality Management System
- ISO 14001: Environmental Management System
- ISO 14064: Greenhouse Gases Emissions Verification
- OHSAS 18001: Occupation Health and Safety Management System





## PRODUCTS

TSM-PE05A  
TSM-PE05A.08


## POWER RANGE

260-270W  
260-270W


## DIMENSIONS OF PV MODULE unit:mm



## I-V CURVES OF PV MODULE (270W)



## P-V CURVES OF PV MODULE (270W)



## ELECTRICAL DATA (STC)

Peak Power Watts- $P_{MAX}$ (Wp)*	260	265	270
Power Output Tolerance- $P_{MAX}$ (W)	0 ~ +5		
Maximum Power Voltage- $V_{MPP}$ (V)	30.6	30.8	30.9
Maximum Power Current- $I_{MPP}$ (A)	8.50	8.61	8.73
Open Circuit Voltage- $V_{OC}$ (V)	38.2	38.3	38.4
Short Circuit Current- $I_{SC}$ (A)	9.00	9.10	9.18
Module Efficiency $\eta_m$ (%)	15.9	16.2	16.5

STC: Irradiance 1000 W/m<sup>2</sup>, Cell Temperature 25°C, Air Mass AM1.5.  
\*Measuring tolerance: ±3%.

## ELECTRICAL DATA (NOCT)

Maximum Power- $P_{MAX}$ (Wp)	193	197	200
Maximum Power Voltage- $V_{MPP}$ (V)	28.4	28.6	28.7
Maximum Power Current- $I_{MPP}$ (A)	6.81	6.89	6.97
Open Circuit Voltage- $V_{OC}$ (V)	35.4	35.5	35.5
Short Circuit Current- $I_{SC}$ (A)	7.27	7.35	7.41

NOCT: Irradiance at 800 W/m<sup>2</sup>, Ambient Temperature 20°C, Wind Speed 1 m/s.

## MECHANICAL DATA

Solar Cells	Multicrystalline 156 × 156 mm (6 inches)
Cell Orientation	60 cells (6 × 10)
Module Dimensions	1650 × 992 × 35 mm (65.0 x 39.1 x 1.38 inches)
Weight	18.6 kg (41.0 lb)
Glass	3.2 mm (0.13 inches), High Transmission, AR Coated Tempered Glass
Backsheet	White
Frame	Silver Anodized Aluminium Alloy (PE05A); Black (PE05A.08)
J-Box	IP 67 or IP 68 rated
Cables	Photovoltaic Technology Cable 4.0mm <sup>2</sup> (0.006 inches <sup>2</sup> ), 1000 mm (39.4 inches)
Connector	MC4(1500V)

## TEMPERATURE RATINGS

Nominal Operating Cell Temperature (NOCT)	44°C (±2°C)
Temperature Coefficient of $P_{MAX}$	-0.41%/°C
Temperature Coefficient of $V_{OC}$	-0.32%/°C
Temperature Coefficient of $I_{SC}$	0.05%/°C

## MAXIMUM RATINGS

Operational Temperature	-40~+85°C
Maximum System Voltage	1500V DC (IEC) 1500V DC (UL)
Max Series Fuse Rating	15A


## WARRANTY

10 year Product Workmanship Warranty  
25 year Linear Power Warranty

(Please refer to product warranty for details)

## PACKAGING CONFIGURATION

Modules per box: 30 pieces  
Modules per 40' container: 840 pieces



TSM\_EN\_2016\_A